

ERGOBJÖRN ESD TROLLEYS



TERMS & FUNCTIONS

Special ESD-protected trolleys for environments with special requirements EPA-ESD-Protected Areas. These trolleys are designed for safe conduction of static electricity. They are approved by RISE Research Institutes of Sweden according to SP-Method 2472, and meet IEC 61340-5-1 and N

100015-1 requirements. The shelves are made of 19 mm conductive panel, melamine-coated on both sides. Black ABS edge strip on all four sides. The shelves and handles are continuously adjustable and can easily be adapted to your needs.

HelgeNyberg

THE PRODUCER OF ERGOBJÖRN



Art. no.	Description
12200306	Brakes on four wheels

ESD SHELF TROLLEY SERIES 100

Max. load: 200 kg. Max. load, shelves: 100 kg. Four swivel wheels measuring 125x32 mm with ball bearing hubs and safety guard.

Extra shelves can be added.

Art. no.	Shelves	Shelf dim.	Length	Width	Height
34112222	2	620x430	800	460	1120
34112322	2	750x430	930	460	1120
34112522	2	1000x430	1180	460	1120
34112622	2	1200x430	1380	460	1120
34112232	3	620x430	800	460	1120
34112332	3	750x430	930	460	1120
34112532	3	1000x430	1180	460	1120
34112632	3	1200x430	1380	460	1120
34112242	4	620x430	800	460	1585
34112342	4	750x430	930	460	1585
34112542	4	1000x430	1180	460	1585
34112642	4	1200x430	1380	460	1585



Load restrainer series 100

Art. no.	Length	Art. no.	Length
12212254	620	12212256	800
12212261	750	12212258	1200
12212262	1000	12212259	1400
12212263	1200	12212260	1600

series 300

Art. no.	Length	Art. no.	Length
12212254	620	12212256	800
12212261	750	12212258	1200
12212262	1000	12212259	1400
12212263	1200	12212260	1600

ESD SHELF TROLLEY SERIES 300

Two fixed wheels and two swivel wheels ensure optimum driving stability. Slightly larger sized wheels combined with a sturdy chassis make this trolley easy to drive even with heavy loads. Max. load: 300 kg. Max. load, lower shelf: 300 kg. Max. load, upper shelves: 100 kg.

Two fixed wheels, two swivel wheels 200x50 mm with roller bearing hubs. Extra shelves can be added.

Model 22 – low ends, 2 shelves

Model 24 – high ends, 4 shelves

Art. no.	Shelves	Shelf dim.	Length	Width	Height
35220623	2	800x620	990	650	1070
35221623	2	1000x620	1190	650	1070
35222623	2	1200x620	1390	650	1070
35224623	2	1400x620	1590	650	1070
35226623	2	1600x620	1790	650	1070
35240643	4	800x620	990	650	1730
35241643	4	1000x620	1190	650	1730
35242643	4	1200x620	1390	650	1730
35244643	4	1400x620	1590	650	1730
35246643	4	1600x620	1790	650	1730





ESD MOBILE TABLE

Chassis of 22 mm round, shiny zinc-coated tubing. Max. load: 100 kg.

Max. load, upper shelf: 100 kg for large table, 50 kg for small table. Four swivel wheels 125x32 mm with ball bearing hubs and safety guard.

Art. no.	Shelves	Shelf dim.	Length	Width	Height
34171120	2	600x430	405	385	1100
34172312	2	820x600	750	430	900
34172612	2	1200x600	750	430	900

If you want the trolley to be delivered unassembled with an approval document enclosed, replace the number 34 with 36 at the beginning of the article number.



ESD TABLE TROLLEY

Chassis made of 22 mm shiny zinc-coated tubing with rounded edges. Max. load: 150 kg. Max. load, upper shelf: 100 kg. Four swivel wheels 125x32 mm with ball bearing hubs and safety guard.

Art. no.	Shelves	Shelf dim.	Length	Width	Height
34734023	2	800x430	1140	460	980
34734033	3	800x430	1140	460	980

If you want the trolley to be delivered unassembled with an approval document enclosed, replace the number 34 with 36 at the beginning of the article number.



ESD BOX DOLLY

Adapted to fit boxes measuring 600x400 mm or 800x600. The rounded frame provides a practical carrying grip. Max. load 400 kg. Four swivel wheels measuring 125x32 mm with ball bearing hubs. Delivered ready-assembled.

Art. no.	Length	Width	Height	Box dimensions
34184826	660	440	180	600x400
34184836	860	640	180	800x600



ESD BOX TROLLEY

Angled 25 mm guide rails for up to 8 boxes 600x400 mm. Height between guide rails 165 mm. Max. load: 200 kg. Four swivel wheels, 125x32 mm with ball bearing hubs.

Art. no.	Length	Width	Height
34119182	670	465	1585

If you want the trolley to be delivered unassembled with an approval document enclosed, replace the number 34 with 36 at the beginning of the article number.



Model 25



SHELF TROLLEY

The ends and shelves are reinforced to withstand loads up to 500 kg. The end uprights are held together by a top element. Lower shelf is recessed in the frame profile. Shelves reinforced with shelf supports. Upper shelves are continuously height-adjustable. Upper shelves have a 25x20 mm edge profile that creates a 10 mm high edge along the lateral sides.

Max. load 500 kg. Lower shelf has a max. load of 500 kg.

Upper shelves have a max. load of 150 kg. Two fixed wheels and two swivel wheels with grey elastic rubber tyres measuring 200x50 mm, ball bearing hubs.

Model 25 – low ends, 2 shelves

Model 27 – high ends, 3 shelves



Model 25

Art nr	Hyllor	Hylldim.	Längd	Bredd	Höjd
15250680	2	800x600	1000	650	1180
15251680	2	1000x600	1200	650	1180
15252680	2	1200x600	1400	650	1180
15253680	2	1230x600	1430	650	1180
15254680	2	1400x600	1600	650	1180
15256680	2	1600x600	1800	650	1180
15251880	2	1000x800	1200	850	1180
15252880	2	1200x800	1400	850	1180
15253880	2	1230x800	1430	850	1180
15254880	2	1400x800	1600	850	1180
15256880	2	1600x800	1800	850	1180

Model 27

Art. no.	Shelves	Shelf dim.	Length	Width	Height
15270680	3	800x600	1000	650	1860
15271680	3	1000x600	1200	650	1860
15272680	3	1200x600	1400	650	1860
15273680	3	1230x600	1430	650	1860
15274680	3	1400x600	1600	650	1860
15276680	3	1600x600	1800	650	1860
15271880	3	1000x800	1200	850	1860
15272880	3	1200x800	1400	850	1860
15273880	3	1230x800	1430	850	1860
15274880	3	1400x800	1600	850	1860
15276880	3	1600x800	1800	850	1860

HelgeNyberg

HEAD OFFICE / SWEDEN

Industrivägen 2
SE-523 90 Ulricehamn

Phone +46 321 263 00
Fax +46 321 263 01

info@helge-nyberg.com
www.helge-nyberg.com

SALES OFFICE / GERMANY

Contact information:
www.helge-nyberg.de